

► **OASIS New Generation Stacked Dryer**

Maximizing Efficiency, Minimizing Footprint



OASIS Stacked Dryer redefines high-volume laundry operations. By integrating two independent drying cylinders into a single, compact footprint, it doubles your productivity without expanding your floor space, offering unparalleled flexibility and control for commercial laundromats.

▼ **Advantages And Benefits**

**Independent Operation & Power Switches**

Equipped with double-screen control and independent power switches, allowing the upper and lower cylinders to work simultaneously without interference.

**Measured Gas Consumption of Less than 400g Per Cycle**

Tested gas consumption for a single cylinder drying cycle is less than 400g (after extraction in a 150G-force washer), ensuring exceptional energy efficiency.

**Stainless Steel Cylinder**

Fully stainless steel cylinders that are rust-proof and prevent fabric scratches during tumbling.

**Service-Friendly Structure**

Designed with a structure that simplifies access for maintenance and repairs, reducing downtime.

**Dual Safety System for Critical Components**

Key components like the thermostat and air damper are equipped with independent switches, providing a dual safeguard with both mechanical and electronic controls.

**Uniquely Designed Fire Tube**

Specially engineered fire tube ensures full and efficient combustion of gas for optimal performance.

**Optimized Exhaust Air Duct Design**

Uniquely designed exhaust duct ensures smoother and more efficient airflow, improving overall drying performance.


**Dual Inverter Motor Drive**

Independent inverter motors for both the drum and the fan, significantly reducing energy consumption and operating costs.

▼ **Double-Screen Control**

Double-screen management for the upper and lower cylinders, offering more flexible and convenient operation to enhance usability. Features networking capabilities for remote monitoring.

Multi-pricing options create additional revenue opportunities. Flexible payment options, including coin, card, mobile pay, and central payment, cater to various business models.



Specifications			HS15
Drying capacity	kg		2*15
Drum Diameter	mm		760
Drum Depth	mm		633
Volume	L		287*2
Gas inlet	inch		1/2"
Power	Drive Motor	kw	2*0.25
	Fan Motor	kw	2*0.25
	Heating Power 220V/380V	kw	2*7.5/2*15
Air flow	m <sup>3</sup> /h		920
Exhaustion	mm		φ 200/7.9"
Drying	r/min		45
Power Supply	v		AC 220/380
Temperature Max	°C		90
Dimension	Width	mm	793
	Depth	mm	1160
	Height	mm	2000
Weight	kg		275

\*OASIS preserves the right to change the machines and specifications at any time without prior notice.

**OASIS**<sup>®</sup>



Jinan Oasis Dry Cleaning and Laundry Equipment Co.,Ltd.

☎ Tel: +86-531-85701288 85711288

✉ E-mail: inquiry@oasisle.com

🌐 Http://www.oasislaundrygroup.com

📍 Add: No.39, Lan Xiang Middle Road, Jinan City, China